

<i>Author</i>	<i>Pasquale Cavone</i>	<i>Date Created</i> 31/01/2022
<i>Client</i>	<i>Internal</i>	<i>Date Edited</i> 02/03/2026
<i>Document</i>	<i>Web Service Easy Tracking</i>	<i>Version</i> 16.0
<i>Reviewer</i>	<i>Leonardo Scardamaglio</i>	

Sommario

1. Document version.....	2
2. Introduction	5
3. Route deprecation plan	6
4. Authentication.....	7
5. Sending electronic invoice and metadata conservation only.....	8
6. List of passive invoices.....	9
7. Download Booking passive invoices.....	12
8. Download Booking passive invoices select type	13
9. Download Zip passive invoices	14
10. Set Phase 1	15
11. Clear Phase 1	16
12. Set Phase 2	17
13. Clear Phase 2.....	18
14. Sending EC notification FPA.....	19
15. List of new notifications FPA.....	20
16. Booking notification FPA download	22
17. Downloading Zip notification FPA	24
18. Mark notification FPA as taken	26
19. Example of a response of a file zip	27
20. Country channel description.....	28
21. Message type notification FPA description	29

1. Document version

Version	Date	Description
4.0	20/01/2023	-New route v2. -In the passive-invoices, query string fields correction.
4.1	20/03/2023	-Added examples of a zip file response.
5.0	11/05/2023	-New route v3. -In the passive-invoices, added phase1, phase2, and top fields to the query string. -In the passive-invoices, enriched the response payload with sdild, dataRicezione and Zilettype. Furthermore, it is possible to provide values for both ReceiverPIVA and ReceiverCF. -New methods: set-fase-1, clear-fase-1, set-fase-2 and clear-fase-2.
5.1	18/05/2023	-Used the camelCase convention for resource names. -Minor corrections to the document.
6.0	19/06/2023	-New route v4. -In the jobs/{jobId} is added filetype "FU" for unsigned invoice. -Used <route> in call description.
7.0	22/11/2023	-New route v5. -New method jobs-select-type. -In the jobs/{jobId} added filetype "FI" for intermediario invoice file.
8.0	03/01/2024	-New route v6. -No changes from v5.
9.0	01/02/2024	-New route v7. -No changes from v6.

		<p>-In the jobs-select-type corrected fatturaOriginale, metadatoSDI, fatturaNonFirmata, fatturaIntermediario are in payload request.</p> <p>-In the passive-invoices corrected invoices instead of invoces.</p>
10.0	12/03/2024	<p>-New route v8.</p> <p>-No changes from v7.</p>
11.0	04/06/2024	<p>-New route v9.</p> <p>-In the passive-invoices added progressivoAnnualeCaricamento and countryChannel.</p>
12.0	13/01/2025	<p>-New route v10.</p> <p>-No changes from v9.</p>
13.0	22/04/2025	<p>-New route v11.</p> <p>-New method PassiveInvoices/fattura-metadato-solo-conservazione.</p> <p>-In DownloadInvoices/passive-invoices added field includeInvoiceConservationOnly in query string.</p> <p>-Added Germany in Country channel description paragraph.</p>
14.0	08/09/2025	<p>-New route v12.</p> <p>-Added route deprecation plan.</p> <p>-New methods for the management of invoice PA notifications:</p> <p>InvoiceNotifications/notifica-fpa/notifica-ec, InvoiceNotifications/notifica-fpa/new-notifications, InvoiceNotifications/notifica-fpa/jobs, InvoiceNotifications/notifica-fpa/jobs/{jobId}, InvoiceNotifications/notifica-fpa/set-notifications-as-got.</p>
15.0	01/10/2025	<p>-New route v13.</p> <p>-Added Belgium in Country channel description paragraph.</p>

16.0	02/03/2026	-New route v14. -Added Poland in Country channel description paragraph.
------	------------	--

2. Introduction

! IMPORTANT: Before using the Web Service calls, contact assistance for the environment configuration.

The Web Service Easy Tracking exposes an interface for downloading the invoices received from SDI on the platform.

Exposed calls:

- The request for a list of passive invoices to download based on certain parameters. It is possible to use the phase 1 field (and/or phase 2) to download only “new” invoices if, after downloading an invoice, you use the set-fase-1 (and/or set-fase-2) method.
- Booking (job) for downloading passive invoices, where n ranges from 1 to 100.
- Download of invoices contained within a job.

Authentication of the calls: Calls must be authenticated according to the OAuth standard through the request of a JWT token and its inclusion as a Bearer token in the header of all calls.

Definition of constants:

The <baseUrl> varies depending on the environments:

VarHub NG production (Empoli) = <https://servizi.varhub.it>

VarHub NG staging (Empoli) = <https://servizitest.varhub.it>

Ditech production (Bologna) = <https://servizi.intermediario.ditechonline.it>

Ditech staging (Bologna) = <https://servizi.intermediariotest.ditechonline.it>

The <authBaseUrl> varies depending on the environments:

VarHub NG production (Empoli) = <https://isentry.varhub.it>

VarHub NG staging (Empoli) = <https://isentrytest.varhub.it>

Ditech production (Bologna) = <https://isentry.intermediario.ditechonline.it>

Ditech staging (Bologna) = <https://isentry.intermediariotest.ditechonline.it>

<route> = v14

3. Route deprecation plan

Routes v3, v5 e v7 are no longer available.

Route	End of maintenance date	Deletion date
v1	Already in end of maintenance	01/03/2026
v2	Already in end of maintenance	01/03/2026
v4	Already in end of maintenance	01/03/2026
v6	Already in end of maintenance	01/03/2026
v8	01/11/2025	01/05/2026
v9	01/04/2026	01/10/2026
v10	01/09/2026	01/03/2027
v11	01/11/2026	01/05/2027
v12	01/03/2027	01/09/2027
v13	01/04/2027	01/10/2027
v14	01/09/2027	

4. Authentication

Web Service to Call	<authBaseUrl>/api/Token/AccessToken
Http Method	POST
Headers	Content-Type: application/json Accept: application/json
Response Status	Status Code: 200 - OK Status Code: 401 - Unauthorized
Payload Request	{ "apiName": "openBusiness.scope.serviziweb.api", "clientName": "openBusiness.client.serviziweb.api", "clientSecret": "uKNtPmq49yjLkaYv", "password": "<password>", "username": "<username>" }
Payload Response	In case of 200: "<token>"
Notes	<username>: username assigned to the client. <password>: password assigned to the client. <token>: JWT token encoded in base64. The response payload is a string that starts and ends with double quotation marks (") enclosing the actual token itself.

5. Sending electronic invoice and metadata conservation only

Web Service to Call	<baseUrl>/api/<route>/PassiveInvoices/fattura-metadato-solo-conservazione
Http Method	POST
Headers	Authorization: Bearer <token> Content-Type: multipart/form-data Accept: application/json
Response Status	Status Code: 200 - OK Status Code: 400 - Bad Request Status Code: 401 - Unauthorized Status Code: 403 - Forbidden: vat number or fiscal code within the invoice for which the user does not have the permissions.
Payload Request	fattura=<fattura> Content-Type: application/octet-stream metadato=<metadato> Content-Type: application/octet-stream
Payload Response	In caso di 200: { "progressivoInvio": <progressivoInvio> } In caso di 400: { "message": <errore> }
Note	<fattura>: fattura in binary format. <metadato>: metadato in binary format. <progressivoInvio> alphanumeric string that uniquely identifies the invoice. It will be used to request the status of the invoice. <errore> explanatory string of the error generated by the request. Intermediary notifications (OI and SI) for the upload result are available in InvoiceNotifications/new-active-notifications method.

6. List of passive invoices

Web Service to Call	<baseUrl>/api/<route>/DownloadInvoices/passive-invoices?field1=value&fieldN=value																						
Http Method	GET																						
Headers	Authorization: Bearer <token> Content-Type: application/json Accept: application/json																						
Response Status	Status Code: 200 - OK Status Code: 400 - Bad Request Status Code: 401 - Unauthorized Status Code: 413 - Payload Too Large (greater than 100000 elementi)																						
Query string	<table border="1"> <thead> <tr> <th>Field</th> <th>Format</th> </tr> </thead> <tbody> <tr> <td>invoiceDateFrom</td> <td>yyyy-MM-dd</td> </tr> <tr> <td>invoiceDateTo</td> <td>yyyy-MM-dd</td> </tr> <tr> <td>invoiceReceivedDateTimeFrom</td> <td>yyyy-MM-dd HH:mm:ss</td> </tr> <tr> <td>invoiceReceivedDateTimeTo</td> <td>yyyy-MM-dd HH:mm:ss</td> </tr> <tr> <td>receiverPIVA</td> <td>string (es. 0200777777)</td> </tr> <tr> <td>receiverCF</td> <td>string</td> </tr> <tr> <td>fase1</td> <td>bool (true/false)</td> </tr> <tr> <td>fase2</td> <td>bool (true/false)</td> </tr> <tr> <td>top</td> <td>Int (<= 100000)</td> </tr> <tr> <td>includeInvoiceConservationOnly</td> <td>bool (true/false)</td> </tr> </tbody> </table>	Field	Format	invoiceDateFrom	yyyy-MM-dd	invoiceDateTo	yyyy-MM-dd	invoiceReceivedDateTimeFrom	yyyy-MM-dd HH:mm:ss	invoiceReceivedDateTimeTo	yyyy-MM-dd HH:mm:ss	receiverPIVA	string (es. 0200777777)	receiverCF	string	fase1	bool (true/false)	fase2	bool (true/false)	top	Int (<= 100000)	includeInvoiceConservationOnly	bool (true/false)
Field	Format																						
invoiceDateFrom	yyyy-MM-dd																						
invoiceDateTo	yyyy-MM-dd																						
invoiceReceivedDateTimeFrom	yyyy-MM-dd HH:mm:ss																						
invoiceReceivedDateTimeTo	yyyy-MM-dd HH:mm:ss																						
receiverPIVA	string (es. 0200777777)																						
receiverCF	string																						
fase1	bool (true/false)																						
fase2	bool (true/false)																						
top	Int (<= 100000)																						
includeInvoiceConservationOnly	bool (true/false)																						
Payload Response	<p>In case of 200:</p> <pre>{ "invoices": [{ "id": <id>, "senderPIVA": "02005004003", "senderCF": "", "receiverPIVA": "0200777777", "receiverCF": "", "data": "2012-04-23", "number": "77/C", "documentType": "TD01", "sdild": "1204005", "dataRicezione": "2012-05-01 09:09:02", "fileName": "filenamefattura.xml p7m", "progressivoAnnualeCaricamento": 24000001, "countryChannel": <countryChannel> }, { "id": <id>,</pre>																						

	<pre> "senderPIVA": "02005088888", "senderCF": "", "receiverPIVA": "02007777777", "receiverCF": "", "data": "2012-04-23", "number": "78/C", "documentType": "TD01", "sdild": "1204006", "dataRicezione": "2012-04-23 19:09:02", "fileName": "filenamefattura.xml p7m", "progressivoAnnualeCaricamento" : 24000102, "countryChannel" : <countryChannel> }, { "total": 3 } In case of 400: { "message": <errore> } </pre>
Notes	<p><id>: unique code (integer) identifier of the invoice to be used in the booking download request.</p> <p><errore>: explanatory string of the error generated by the request.</p> <p><countryChannel>: (integer) document origin country (see Country channel description section).</p> <p>In the Request:</p> <ul style="list-style-type: none"> - The date range cannot exceed 31 days. Only one type of date range can be specified, either document date or received date. - It is possible to provide a value for either VAT Number (PIVA) or fiscal code (CF), or neither of them, or both - if phase1 and/or phase2, the allowed date range extends to 365 days.

	<ul style="list-style-type: none">- if Top is not specified, it is assumed to be equal to 100000.- if includeInvoiceConservationOnly specified and equal to false then invoices conservation only will be excluded from the list.
--	--

7. Download Booking passive invoices

Web Service to Call	<baseUrl>/api/<route>/DownloadInvoices/jobs
Http Method	POST
Headers	Authorization: Bearer <token> Content-Type: application/json Accept: application/json
Response Status	Status Code: 202 - Accepted Status Code: 400 - Bad Request Status Code: 401 - Unauthorized Status Code: 403 - Forbidden
Payload Request	List of document ids, max 100 { "docIds": [id1, id2, ..., id100] }
Payload Response	In case of 202: { "jobId": <jobId> } In case of 400: { "message": <errore> }
Notes	<jobId>: 36-character string (GUID) that should be used in job status requests. Once the job is created, it has a validity of 24 hours. After that, it will be deleted even if not downloaded. <errore>: explanatory string of the error generated by the request. Job created with fileType "FA", "MT", "FU"

Response Status

HTTP 202 (Accepted): job in progress

HTTP 400 (Bad Request): invalid input data

HTTP 401 (Unauthorized): invalid token

HTTP 403 (Forbidden): one or more document ids not found or for which the user does not have permissions

8. Download Booking passive invoices select type

Web Service to Call	<baseUrl>/api/<route>/DownloadInvoices/jobs-select-type
Http Method	POST
Headers	Authorization: Bearer <token> Content-Type: application/json Accept: application/json
Response Status	Status Code: 202 - Accepted Status Code: 400 - Bad Request Status Code: 401 - Unauthorized Status Code: 403 - Forbidden
Payload Request	List of document ids, max 100 { "docIds": [id1, id2, ..., id100], "fatturaOriginale": <bool>, "metadatoSDI": <bool>, "fatturaNonFirmata": <bool>, "fatturaIntermediario": <bool> }
Payload Response	In case of 202: { "jobId": <jobId> } In case of 400: { "message": <errore> }
Notes	<jobId>: 36-character string (GUID) that should be used in job status requests. Once the job is created, it has a validity of 24 hours. After that, it will be deleted even if not downloaded. <bool>: true o false <errore>: explanatory string of the error generated by the request. Matching payload parameters with fileType: - "fatturaOriginale": "FA" - "metadatoSDI": "MT" - "fatturaNonFirmata": "FU" - "fatturaIntermediario": "FI"

Response Status

HTTP 202 (Accepted): job in progress

HTTP 400 (Bad Request): invalid input data or "fatturaOriginale", "metadatoSDI", "fatturaNonFirmata", "fatturaIntermediario" are all false

HTTP 401 (Unauthorized): invalid token

HTTP 403 (Forbidden): one or more document ids not found or for which the user does not have permissions

9. Download Zip passive invoices

Web Service to Call	<baseUrl>/api/<route>/DownloadInvoices/jobs/{jobId}
Http Method	GET
Headers	Authorization: Bearer <token> Content-Type: application/json Accept: application/json
Response Status	Status Code: 200 - OK Status Code: 202 - Accepted Status Code: 400 - Bad Request Status Code: 401 - Unauthorized Status Code: 403 - Forbidden
Payload Request	
Payload Response	File Zip
Notes	

Response Status

HTTP 202 (Accepted): job in progress

HTTP 400 (Bad Request): invalid input data (invalid GUID)

HTTP 401 (Unauthorized): invalid token

HTTP 403 (Forbidden): GUID not found or for which the user does not have permissions

HTTP 200 (OK): The response contains a zip file with the invoice files and an indice.json file. The job will be reset after the response. To be able to download it again, a new job must be created. The payload of the response is a binary file with the content type application/octet-stream.

The indice.json file contains the list of invoices inside the zip file, indicating for each the id, the fileName and the fileType.

The fileType can have the following values:

- "FA": original invoice received from SDI (xml or p7m)
- "MT": SDI metadata
- "FU": unsigned invoice
- "FI": intermediario invoice

10. Set Phase 1

Web Service to Call	<baseUrl>/api/<route>/PassiveInvoices/set-fase-1
Http Method	POST
Headers	Authorization: Bearer <token> Content-Type: application/json Accept: application/json
Response Status	Status Code: 200 - OK Status Code: 400 - Bad Request Status Code: 401 - Unauthorized Status Code: 403 - Forbidden
Payload Request	List of document ids, max 100 { "docIds": [id1, id2, ..., id100] }
Payload Response	In case of 400: { "message": <errore> }
Notes	

Response Status

HTTP 200 (OK): operation executed

HTTP 400 (Bad Request): invalid data input

HTTP 401 (Unauthorized): invalid token

HTTP 403 (Forbidden): one or more document ids not found or for which the user does not have permissions

11. Clear Phase 1

Web Service to Call	<baseUrl>/api/<route>/PassiveInvoices/clear-fase-1
Http Method	POST
Headers	Authorization: Bearer <token> Content-Type: application/json Accept: application/json
Response Status	Status Code: 200 - OK Status Code: 400 - Bad Request Status Code: 401 - Unauthorized Status Code: 403 - Forbidden
Payload Request	List of document ids, max 100 { "docIds": [id1, id2, ..., id100] }
Payload Response	In case of 400: { "message": <errore> }
Notes	

Response Status

HTTP 200 (OK): operation executed

HTTP 400 (Bad Request): invalid data input

HTTP 401 (Unauthorized): invalid token

HTTP 403 (Forbidden): one or more document ids not found or for which the user does not have permissions

12. Set Phase 2

Web Service to Call	<baseUrl>/api/<route>/PassiveInvoices/set-fase-2
Http Method	POST
Headers	Authorization: Bearer <token> Content-Type: application/json Accept: application/json
Response Status	Status Code: 200 - OK Status Code: 400 - Bad Request Status Code: 401 - Unauthorized Status Code: 403 - Forbidden
Payload Request	List of document ids, max 100 { "docIds": [id1, id2, ..., id100] }
Payload Response	In case of 400: { "message": <errore> }
Notes	

Response Status

HTTP 200 (OK): operation executed

HTTP 400 (Bad Request): invalid data input

HTTP 401 (Unauthorized): invalid token

HTTP 403 (Forbidden): one or more document ids not found or for which the user does not have permissions

13. Clear Phase 2

Web Service to Call	<baseUrl>/api/<route>/PassiveInvoices/clear-fase-2
Http Method	POST
Headers	Authorization: Bearer <token> Content-Type: application/json Accept: application/json
Response Status	Status Code: 200 - OK Status Code: 400 - Bad Request Status Code: 401 - Unauthorized Status Code: 403 - Forbidden
Payload Request	List of document ids, max 100 { "docIds": [id1, id2, ..., id100] }
Payload Response	In case of 400: { "message": <errore> }
Notes	

Response Status

HTTP 200 (OK): operation executed

HTTP 400 (Bad Request): invalid data input

HTTP 401 (Unauthorized): invalid token

HTTP 403 (Forbidden): one or more document ids not found or for which the user does not have permissions

14. Sending EC notification FPA

Web Service to Call	<baseUrl>/api/<route>/InvoiceNotifications/notifica-fpa/notifica-ec
Http Method	POST
Headers	Authorization: Bearer <token> Content-Type: multipart/form-data Accept: application/json
Response Status	Status Code: 200 - OK Status Code: 400 - Bad Request Status Code: 401 - Unauthorized Status Code: 403 - Forbidden: sdild within the notification for which the user does not have the permissions
Payload Request	notifica=<notifica> Content-Type: application/octet-stream
Payload Response	In case of 200: { "progressivoInvio": <progressivoInvio> } In case of 400: { "message": <errore> }
Note	<notifica>: notification in binary format. <progressivoInvio>: alphanumeric string that uniquely identifies the notification. <errore>: explanatory string of the error generated by the request.

15. List of new notifications FPA

Web Service to call	<baseUrl>/api/<route>/InvoiceNotifications/notifica-fpa/new-notifications?field1=value&fieldN=value					
Http Method	GET					
Headers	Authorization: Bearer <token> Content-Type: application/json Accept: application/json					
Response Status	Status Code: 200 - OK Status Code: 400 - Bad Request Status Code: 401 - Unauthorized Status Code: 413 - Payload Too Large (greater than 100000 elements)					
Query string	<table border="1"> <thead> <tr> <th>Field</th> <th>Format</th> </tr> </thead> <tbody> <tr> <td>top</td> <td>int (<= 100000)</td> </tr> </tbody> </table>		Field	Format	top	int (<= 100000)
Field	Format					
top	int (<= 100000)					
Payload Response	In case of 200: <pre>{ "notifications": [{ "notificationId": <notificationId>, "progressivoInvio": <progressivoInvio>, "fileName": "filenamenotifica.xml", "tipoMessaggio": <tipoMessaggio>, "sdild": "<sdild>" }, { "notificationId": <notificationId>, "progressivoInvio": <progressivoInvio>,</pre>					

	<pre> “fileName”: “filenamenotifica.xml”, “tipoMessaggio”: <tipoMessaggio>, “sdild”: “<sdild>” }], “total”: 2 } In case of 400: { “message”: <errore> } </pre>
<p>Note</p>	<p><notificationId>: unique code (integer) notification identifier to be used in the download booking request.</p> <p><progressivoInvio>: unique code of notification upload. Not assigned in case of DT notification.</p> <p><fileName>: file name of notification. Assigned for DT and SE notification only.</p> <p><tipoMessaggio>: notification type (see Message type notification FPA description section).</p> <p><sdild>: sdild of notification.</p> <p><errore>: explanatory string of the error generated by the request.</p> <p>In the Request:</p> <ul style="list-style-type: none"> - If top is not specified, it is assumed to be equal to 100000.

16. Booking notification FPA download

Web Service to call	<baseUrl>/api/<route>/InvoiceNotifications/notifica-fpa/jobs
Http Method	POST
Headers	Authorization: Bearer <token> Content-Type: application/json Accept: application/json
Response Status	Status Code: 202 - Accepted Status Code: 400 - Bad Request Status Code: 401 - Unauthorized Status Code: 403 - Forbidden
Payload Request	List of notification ids, max 100 <pre>{ "notificationIds": [id1, id2, ..., id100] }</pre>
Payload Response	In case of 202: <pre>{ "jobId": <jobId> }</pre> In case of 400: <pre>{ "message": <errore> }</pre>
Note	<jobId>: 36-character string (GUID) that should be used in job status requests. Once the job is created, it has a validity of 24 hours. After that, it will be deleted even if not downloaded. <errore>: explanatory string of the error generated by the request.

Response Status

HTTP 202 (Accepted): job in progress

HTTP 400 (Bad Request): invalid input data

HTTP 401 (Unauthorized): invalid token

HTTP 403 (Forbidden): one or more notificationIds not found or for which the user does not have permissions

17. Downloading Zip notification FPA

Web Service to call	<baseUrl>/api/<route>/InvoiceNotifications/notifica-fpa/jobs/{jobId}
Http Method	GET
Headers	Authorization: Bearer <token> Content-Type: application/json Accept: application/json
Response Status	Status Code: 200 - OK Status Code: 202 - Accepted Status Code: 400 - Bad Request Status Code: 401 - Unauthorized Status Code: 403 - Forbidden
Payload Request	
Payload Response	Zip File
Note	

Response Status

HTTP 202 (Accepted): job in progress

HTTP 400 (Bad Request): invalid data input (invalid GUID)

HTTP 401 (Unauthorized): invalid token

HTTP 403 (Forbidden): GUID not found or for which the user does not have permissions

HTTP 200 (OK): the response contains a zip file with the notification files and an indice.json file. the job will be reset after the response. To be able to download it again, a new job must be created. The response payload is a binary file with the content type application/octet-stream.

The indice.json file contains the list of notifications inside the zip file, indicating for each the notificationId, progressivoInvio, fileName, tipoMessaggio and sdild.

Example of the content of the indice.json file:

```
{
```

```
"files": [  
  {  
    "notificationId": 123,  
    "progressivoInvio": 1357,  
    "fileName": null,  
    "tipoMessaggio": 0,  
    "sdild": 151081  
  },  
  {  
    "notificationId": 124,  
    "progressivoInvio": null,  
    "fileName": " filenamenotifica_DT.xml",  
    "tipoMessaggio": 3,  
    "sdild": "1234567"  
  },  
  {  
    "notificationId": 125,  
    "progressivoInvio": 1358,  
    "fileName": " filenamenotifica_SE.xml",  
    "tipoMessaggio": 2,  
    "sdild": "9876543"  
  }  
]  
}
```

18. Mark notification FPA as taken

Web Service to call	<baseUrl>/api/<route>/InvoiceNotifications/notifica-fpa/set-notifications-as-got
Http Method	POST
Headers	Authorization: Bearer <token> Content-Type: application/json Accept: application/json
Response Status	Status Code: 200 - OK Status Code: 400 - Bad Request Status Code: 401 - Unauthorized Status Code: 403 - Forbidden
Payload Request	Lista di id notifiche, max 100 <pre>{ "notificationIds": [id1, id2, ..., id100] }</pre>
Payload Response	In caso di 400: <pre>{ "message": <errore> }</pre>
Note	

Response Status

HTTP 200 (OK): operation executed








HTTP 400 (Bad Request): invalid data input

HTTP 401 (Unauthorized): invalid token

HTTP 403 (Forbidden): one or more notification ids not found or for which the user does not have permissions

19. Example of a response of a file zip

Content of the zip file

Name	Date modified	Type	Size
 IT07031780484_4582619.xml	19/06/2023 15:43	XML File	12 KB
 IT07031780484_4581939.xml	19/06/2023 15:43	XML File	78 KB
 20230619_152243878.ef_IT016417907022023Y_05Xa6_MT_001.xml	19/06/2023 15:43	XML File	1 KB
 20230619_152243878.ef_IT016417907022023Y_05Xa6.xml	19/06/2023 15:43	XML File	12 KB
 20230619_141959147.a7_IT06628860964_9FKju_MT_001.xml	19/06/2023 15:44	XML File	1 KB
 20230619_141959147.a7_IT06628860964_9FKju.xml.p7m	19/06/2023 15:43	P7M File	83 KB
 indice.json	19/06/2023 15:48	JSON File	1 KB

Content of the indice.json file:

```
{
  "files": [
    {
      "id": 4574622,
      "fileName": "20230619_141959147.a7_IT06628860964_9FKju.xml.p7m",
      "fileType": "FA"
    },
    {
      "id": 4574622,
      "fileName": "20230619_141959147.a7_IT06628860964_9FKju_MT_001.xml",
      "fileType": "MT"
    },
    {
      "id": 4574622,
      "fileName": "IT07031780484_4581939.xml",
      "fileType": "FU"
    },
    {
      "id": 4575300,
      "fileName": "20230619_152243878.ef_IT016417907022023Y_05Xa6.xml",
      "fileType": "FA"
    },
    {
      "id": 4575300,
      "fileName": "20230619_152243878.ef_IT016417907022023Y_05Xa6_MT_001.xml",
      "fileType": "MT"
    },
    {
      "id": 4575300,
      "fileName": "IT07031780484_4582619.xml",
      "fileType": "FU"
    }
  ]
}
```

20. Country channel description

Value	Description
0	Italy
1	Rumania
2	Germany
3	Belgium
4	Poland

21. Message type notification FPA description

Value	Description
0	EC notification accepted from SDI
1	EC notification sent to SDI but require manual check
2	SE notification
3	DT notification